

PAGATTI

Žica vzmetna patentirana

ŽICA EN 10218-2:1996
JEKLO EN 10270-1:2001

Premer d mm	Teža kg/1000 m	Trdnost za vzmetne žice			
		SL R _m - MPa	SM R _m - MPa	SH R _m - MPa	DH R _m - MPa
0,30	0,55		●2370-2650		○2260-2940
0,35	0,75		●2310-2580		○2590-2870
0,40	1,00		●2270-2550		○2560-2830
0,45	1,20		●2240-2500		○2510-2780
0,50	1,50		●2200-2470		○2480-2740
0,55	1,90		●2170-2430		○2440-2700
0,60	2,20		●2140-2400		○2410-2670
0,70	3,00		●2090-2350		○2360-2610
0,80	3,90		●2050-2300		●2310-2560
0,90	5,00		●2010-2260		○2270-2510
1,00	6,20	○1720-1970	●1980-2220		●2230-2560
1,10	7,50	○1690-1940	●1950-2190		○2200-2430
1,20	8,90	○1670-1910	●1920-2160		●2170-2400
1,30	10,40	○1640-1890	●1900-2130		○2140-2370
1,40	12	○1620-1860	●1870-2100		○2110-2340
1,50	14	○1600-1840	●1850-2080		●2090-2310
1,60	16	○1590-1820	●1830-2050		○2060-2290
1,80	20	○1550-1780	●1790-2010		●2020-2240
2,00	25	○1520-1750	●1760-1970	●1980-2200	
2,20	30	○1490-1710	○1720-1930	●1940-2150	
2,50	39	○1460-1680	●1690-1890	●1900-2110	
2,80	48	○1420-1640	○1650-1850	●1860-2070	
3,00	55	○1410-1620	●1630-1830	●1840-2040	
3,20	63	○1390-1600	○1610-1810	●1820-2020	
3,40	71	○1370-1580	○1590-1780	●1790-1990	
3,50	75	○1350-1560	○1570-1760	●1770-1970	
3,60	80	○1350-1560	○1570-1760	●1770-1970	
3,80	89	○1340-1540	○1550-1740	●1750-1950	
4,00	99	○1320-1520	○1530-1730	●1740-1930	
4,20	109	○1310-1500	○1510-1700	●1710-1900	
4,50	125	○1290-1490	○1500-1680	●1690-1880	
5,00	154	○1260-1450	○1460-1650	●1660-1840	
5,30	174	○1240-1430	○1440-1630	●1640-1820	
5,50	187	○1230-1420	○1430-1610	●1620-1800	
5,60	194	○1230-1420	○1430-1610	●1620-1800	
6,00	222	○1210-1390	○1400-1580	●1590-1770	
6,50	260	○1180-1370	○1380-1550	●1560-1740	
7,00	302	○1160-1340	○1350-1530	●1540-1710	
8,00	395	○1120-1300	○1310-1480	●1490-1660	
9,00	499	○1090-1260	○1270-1440	●1450-1610	
10,00	617	○1060-1230	○1240-1400	●1410-1570	
11,00	746		○1210-1370	●1380-1530	
12,00	888		○1180-1340	●1350-1500	